


Chip Inductor (Chip Coil) Power Inductor (Multilayer Type)

LQM18P_FR Series (0603 Size)

■ Dimensions



■ Packaging


Code	Packaging	Minimum Quantity
L	180mm Embossed Tape	4000
B	Bulk(Bag)	1000

■ Rated Value (□: packaging code)


Part Number	Inductance	Rated Current	DC Resistance	Self Resonance Frequency (min.)
LQM18PNR22NFR□	0.22μH±30%	1250mA	0.11ohm ±25%	100MHz
LQM18PNR47NFR□	0.47μH±30%	1100mA	0.15ohm ±25%	100MHz
LQM18PN1R0MFR□	1.0μH±20%	950mA	0.20ohm ±25%	100MHz
LQM18PN1R5MFR□	1.5μH±20%	800mA	0.23ohm ±25%	100MHz
LQM18PN2R2MFR□	2.2μH±20%	750mA	0.30ohm ±25%	70MHz
LQM18PN3R3MFR□	3.3μH±20%	700mA	0.35ohm ±25%	60MHz
LQM18PN4R7MFR□	4.7μH±20%	620mA	0.44ohm ±25%	40MHz

Test Frequency: 1MHz Class of Magnetic Shield: Magnetic shield of ferrite Operating Temperature Range: -40 to +85°C

■ Inductance-Frequency Characteristics (Typ.)



■ Inductance-Current Characteristics (Typ.)




Continued on the following page.


● This data sheet is applied for CHIP INDUCTORS (CHIP COILS) used for General Electronics equipment for your design.

⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

 Continued from the preceding page.

■ Temperature Rise Characteristics (Typ.)



■ ⚠ Caution/Notice

⚠ Caution (Rating)

Do not use products beyond the rated current as this may create excessive heat.

Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

● This data sheet is applied for CHIP INDUCTORS (CHIP COILS) used for General Electronics equipment for your design.

⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.