Crystal Units
Surface Mount Type CX1255GB (CX-5FD)

KYOCERA

11.8×5.5mm for Consumer Products

RoHS Compliant

Features

- Crystal unit for Consumer Products
- Small and low profile (11.8×5.5×1.8mm)
- Ceramic package
- Reflow compatible

Applications

- Digital Electronics
- Consumer Products
- Car audio and accessories

How to Order

CX1255GB 04000 □□ □ □ □ □□

① ② ③ ④ ⑤ ⑥ ⑦

① Series ② Frequency
③ Load Capacitance ④ Frequency Tolerance

H0	12 pF	P	$\pm50\times10^{-6}$

⑤ Operating Temp. Range ⑥ Frequency Temp. Stability

ES	−10 to +70°C	$\pm50\times10^{-6}$

⑦ Individual Specification

Packaging (Tape & Reel 1000 pcs./ reel)

Specifications

Item	Symbol	Specification	Units	Remarks
Frequency Range	f_{nom}	3500 to 29000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	
Frequency Tolerance	f_{tol}	±50	$\times10^{-6}$	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T_{use}	−10 to +70	°C	
Storage Temp. Range	T_{stg}	−40 to +85	°C	
Frequency Temp. Characteristics	f_{tem}	±50	$\times10^{-6}$	Freq. deviation from the value at 25°C

• Please contact us for other specifications.

Table1 Motional Series Resistance

Frequency Range	Motional Series Resistance
$3500 \le f_{nom} < 4000$kHz	200Ω max.
$4000 \le f_{nom} < 8000$kHz	180Ω max.
$8000 \le f_{nom} < 12000$kHz	120Ω max.
$12000 \le f_{nom} \le 29000$kHz	80Ω max.

Table2 Level of Drive

Frequency Range	Level of Drive
$3500 \le f_{nom} < 16000$kHz	10μW (500μW max.)
$16000 \le f_{nom} < 25000$kHz	10μW (300μW max.)
$25000 \le f_{nom} \le 29000$kHz	10μW (100μW max.)

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)